

ST = Number	Breaking Strength	Maximum Tension Rating	StandardCordDiameter	StandardCordPitch	Standard CoverThickness	In Case ofStandard Cover				
Top Cover	ButtomCover	BeltThickness	BeltWeight							
	lbs / inkg / cm	lbs / inkg / cm	inmm	inmm	inmm	inmm	inmm	lbs / ft²kg / m²		
ST-500	2	800500	40071.4	0.0872.20	0.39410.0	0.1975.0	0.1975.0	0.48012.2	3.3416.3	
ST-600	3	360600	48085.7	0.0962.45	0.39410.0	0.1975.0	0.1975.0	0.49012.5	3.4616.9	
ST-630	3	530630	50490	0.0982.50	0.39410.0	0.1975.0	0.1975.0	0.49012.5	3.5217.2	
ST-700	3	920700	560100	0.1062.70	0.39410.0	0.1975.0	0.1975.0	0.50012.7	3.6017.6	
ST-800	4	480800	640114.2	0.1142.90	0.39410.0	0.1975.0	0.1975.0	0.50812.9	3.7518.3	
ST-900	5	40900	720128.5	0.1223.10	0.39410.0	0.1975.0	0.1975.0	0.51613.1	3.6717.9	
ST-1000	5	6001000	800157.1	0.1423.60	0.47212.0	0.1975.0	0.1975.0	0.53513.6	3.9319.2	
ST-1100	6	1601100	880157.1	0.1503.80	0.47212.0	0.1975.0	0.1975.0	0.54313.8	4.0119.6	
ST-1200	6	7201200	960171.4	0.1563.95	0.47212.0	0.1975.0	0.1975.0	0.55114.0	4.1420.2	
ST-1250	7	1250	1	178.6	0.1574.00	0.47212.0	0.1975.0	0.1975.0	0.55114.0	4.2020.5
ST-1300	7	2801300	1	40185.7	0.1614.10	0.47212.0	0.1975.0	0.1975.0	0.55514.1	4.2720.8
ST-1400	7	8401400	1	120200	0.1694.30	0.47212.0	0.1975.0	0.1975.0	0.56314.3	4.3921.4
ST-1500	8	4001500	1	200214.3	0.1764.40	0.47212.0	0.2366.0	0.2366.0	0.64616.4	5.0024.4
ST-1600	8	9601600	1	280228.6	0.1814.60	0.47212.0	0.2366.0	0.2366.0	0.65416.6	5.2225.5
ST-1700	9	5201700	1	360242.8	0.1894.80	0.47212.0	0.2366.0	0.2366.0	0.66116.8	5.3226
ST-1800	10	801800	1	440257.1	0.1975.00	0.47212.0	0.2366.0	0.2366.0	0.66917.0	5.4926.8
ST-1900	10	6401900	1	520.271.4	0.2015.00	0.47212.0	0.2366.0	0.2366.0	0.67317.1	5.5126.9
ST-2000	11	2002000	1	600285.7	0.2055.20	0.47212.0	0.2366.0	0.2366.0	0.67717.2	5.7227.9
ST-2100	11	7602100	1	680300	0.2205.60	0.59112.0	0.2767.0	0.2767.0	0.77219.6	6.1029.8
ST-2200	12	3202200	1	760314.2	0.2285.80	0.59112.0	0.2767.0	0.2767.0	0.78019.8	6.2630.5
ST-2300	12	8802300	1	840328.5	0.2325.90	0.59112.0	0.2767.0	0.2767.0	0.78319.9	6.3330.9
ST-2400	13	4402400	1	920342.8	0.2366.00	0.59112.0	0.2767.0	0.2767.0	0.78720.0	6.4531.5
ST-2500	14	2500	2	357.1	0.2446.20	0.59112.0	0.2767.0	0.2767.0	0.79520.2	6.6232.3